

# **Key Features**

• Speed: 260mm/sec

• Print width: 80mm

• Print head life: 150km

• Connectivity: USB + Serial + Lan

Printing	IHR-810
Printing Method	Direct Thermal
Printing Width	80mm
Resolution	203 dpi
Printing Speed	260 mm/s
Interface	USB+Serial+Lan / Bluetooth / WiFi Optional
Printing Paper	79.5±0.5mm x Ø80mm
Line Spacing	3.75mm (Adjustable by commands)
<b>Printer Command</b>	ESC/POS
Font	80mm paper : Font A - 42 columns or 48 columns/ Font B - 56 columns or 64 columns/
Character Size	ANK, Font A: 12x24 dots Font B: 9x17 dots

## **Barcode Character**

1D Code UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE98

/CODE128

**2D Code** QR Code / PDF417

Buffer

Input Buffer128 kbNV Flash256 kb

Power

Power Adaptor AC: 100-240V, 50~60Hz Power Source Output: DC 24V/2.5A

Cash Drawer Output DC 24V/1A

# **Physical characteristics**

Weight 1Kg

**Dimensions (DxWxH)**  $190 \times 140 \times 135 \text{ mm}$ 

## **Enviromental Requirements**

**Work Environment** Temperature (0~45°C), Humidity (10~80%) (Non-Condensing)

**Storage Environment** Temperature (-10~60°C), Humidity (10~90%)

Reliability

**Auto Cutter Life** 1.5 million cuts

Printer Head Life 150KM

**Driver** Win 9X / Win 2000 / Win 2003 / Win XP / Win 7 / Win 8 / Win 10 / Linux / MAC

## Honeywell International India Pvt. Ltd.

1120–21, 11th Floor, Tower A, DLF Tower, Jasola, Jasola District Centre New Delhi – 110025, India

Toll Free Number: 1800-890-7447





V-1-AUG 22