HONEYWELL VERTEXT EDGE

Toxic Gas Monitoring System

Go low. Get advanced low-level detection and a lower cost of ownership.

Honeywell VertexTM Edge delivers the reliable performance and versatility of Honeywell VertexTM — with a lower cost and easier experience. To help you protect people and assets while reducing downtime, Honeywell VertexTM Edge provides:

- Authentic Chemcassette® technology for enhanced standard of accuracy
 The system detects highly toxic gases quickly and definitively down to parts
 per billion (ppb) as evidenced by a clear, easy-to-view stain on chemically
 treated tape. This technology, pioneered by Honeywell, delivers low-level
 gas detection you can count on.
- Monitoring of more than 40 toxic gases

 Start with as few as eight sampling points and add up to 72. Place each point up to 400 feet (120 meters) away for flexible reach.
- Lower cost of ownership
 Get a lower system price than Honeywell Vertex™ plus Chemcassette® tapes for ammonia, hydrides and mineral acids that last six months instead of the usual three. That means double the usage at a lower operating cost.
- Smart, intuitive interface for enhanced performance and simple operation Touchscreen and large icons make it easy to see gas readings, alarms, event logs, real-time trends and overall system status. Minimal training required.



MORE FEATURES & BENEFITS

Straightforward maintenance to reduce costly downtime:

FRONT ACCESS

Easily service the power and data cables with a clear view of the touchscreen and Chemcassette® analyzers. Pullout tray makes it easy to replace and service pumps.

NO-SCREW SERVICE PANELS

Access the inside of the unit with keylock and latch - no screwdriver needed.

SIMPLIFIED OUTPUT

Vertex Edge offers Modbus TCP and Modbus RTU for interfacing to your sites control systems.

SMART REMINDERS

Use the touchscreen to set customized reminders for maintenance tasks; clearly see which elements to service.

EASY TUBE MANAGEMENT

Quickly identify sampling tubes for corresponding analyzers, so you can address a fault or install a new point.

DURABLE DESIGN

Steel door stands up to traffic, while a splash-proof cap protects the system from overhead liquid exposure.



VERTEX SESPECIFICATION SHEET

76" x 24" x 35"
~900lbs (~408kg)
~655lbs (~297kg)
22" x 13" x 6"
≤ 27lbs (12kg)
208V~240VAC,15A
1.1kWatt
≤ 1.4k Watt
15.6" wide screen monitor with capacitive touch interface Display gas reading, alarm & instrument status real-time base Provide real-time trend chart and gas event snapshot trend chart
Event logging including maintenance/instrument fault and gas alarm Multiple searching option for the event LED indicator: Normal (Green), Alarm 1 (Red), Alarm 2 (Red), Fault (Yellow)
TCP/IP and RTU Modbus, OPC (Option)
Role-based access control Support HTTPS
EN 50270 and EN61010-1 UL/IEC 61010-1 RED, FCC for RFID
Refer to product manual for complete gas list
2.1 LPM
Less than 50 seconds up to 325ft with thin wall tube (0.190"ID)
1/4 in. (6.35 mm) 0.D. x 0.190in. (4.83 mm) (Thin wall)
Up to 400ft (120m) with thin wall
1/2 in. (12.7 mm) 0.D. x 3/8 in. (9.5 mm) I.D. Teflon tubing
Up to 50 ft. (15 m) maximum
59°F to 95°F (15°C to 35°C)
20-80% RH
-1000 ft. (-305 m) to 6000 ft. (1829 m) above sea level
2
Single phase power, Minimum 14 AWG
Modbus TCP/IP: CAT5 shielded cable or equivalent (RJ45 connector);
Modbus RTU: 2-wire stranded, shielded cable or equivalent (24-14 AWG)

For more information honeywellanalytics.com

Asia Pacific, India

Mainland China

analytics.ap@honeywell.com

Americas

detectgas@honeywell.com

Taiwan

analytics.tw@honeywell.com

gaschina@honeywell.com

Europe, Middle East, Africa gasdetection@honeywell.com

HON_DTS_VERTEX-EDGE_A4_EN-0820 | 08/20
© 2020 Honeywell International Inc.

Honeywell

Honeywell

WHAT