



Safety and Productivity Solutions

9680 Old Bailes Road
Fort Mill, SC 29707 USA

www.honeywell.com www.honeywellaidc.com

DECLARATION OF CONFORMITY

Manufacturers' Name: Honeywell International Inc Safety and Productivity Solutions 9680 Old Bailes Road Fort Mill, SC 29707 USA	European Representative: Honeywell International Inc Honeywell Productivity Solutions BV Lagelandseweg 70 6545 CG Nijmegen The Netherlands Phone: +31 (0) 24 3723100
---	--

Honeywell declares under its sole responsibility that the Honeywell products described below conform to Directive 2011/65/EU of the European Parliament and of the Council of 8 June 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment, as amended - including (EU) 2015/863 of 31 March 2015 amending Annex II.

This declarations applies to the Restricted Substances referred to in the Annex of (EU) 2015/863.

Substance	Maximum Concentration Value
Lead (Pb)	0.1%
Mercury (Hg)	0.1%
Cadmium (Cd)	0.01%
Hexavalent chromium (Cr6+)	0.1%
Polybrominated biphenyls (PBB)	0.1%
Polybrominated diphenyl ethers (PBDE)	0.1%
Bis(2-ethylhexyl) phthalate (DEHP)	0.1%
Butyl benzyl phthalate (BBP)	0.1%
Dibutyl phthalate (DBP)	0.1%
Diisobutyl phthalate (DIBP)	0.1%

Referenced harmonized standards and/or technical specifications:

EN 50581:2012 "Technical documentation for the assessment of electrical and electronic products with respect to the restriction of hazardous substances"
--

Additional information:

None



Safety and Productivity Solutions

9680 Old Bailes Road
Fort Mill, SC 29707 USA

www.honeywell.com www.honeywellaidc.com

DECLARATION OF CONFORMITY

Honeywell Safety and Productivity Solutions Products:

162829-0001	CBL, MPP USB ADPTR
162830-0001	CBL, MPP RS232 ADPTR
162831-0001	CBL, MPP RS232+USB
19-00121	Cable, Straight, Black
19-00122B-3	Cable, Black, Coio 9'
19-00123	Cable, black, USB type A
19-00142C-3	CBL Black 10 Cond Shield
19-00239A-3-10	RS232 cable PWR
19-00264C	Cable, 4225, Shielded Head
19-00277B	Cable, 4225, Head, Dual 8
19-00307-3	Cable MVC Dual Ended 10
19-00314B-3	Cable, Dual Ended USB
19-00335A-3	Cable, Dual Ended Male
19-00336A-3	Cable, Dual Ended RJ
19-00339A-3	Cable, Dual End, DB9
19-00341A-3	Cable, Dual End, USB, Black
19-00362A-3	USB Multi Checkpoint
19-19670	Cable 14 COND SHLD W/DRA
19-19671	Cable, 8 COND, Shield
19-19753B	CBL KEYWEDGE HEAD W/GRO
19-19825B	Cable, Pwrlnk, Straight
19-19825B-3	Cable, pwrlnk, straight
19-19826	Cable, USB Type A
19-19827A	Cable, Pwrlnk, coiled
41203757-05	CBL, MOD DEC W/NO CONN
41203757-06	CBL, MOD W/O CONN.
41203757-07	CBL, MOD BI W/NO CONN
41205223-05	CBL, 3400+12V CORE ENG
41205571-03	CBL, 10 COND CORE ENGINE
42203758-01E	Cable: RS232 TTL, Power on Pin 9, TX Data on Pin 2 Connector: D 9 PIN M Length: 7.7 ft. (2.4m), coiled



Safety and Productivity Solutions

9680 Old Bailes Road
Fort Mill, SC 29707 USA

www.honeywell.com www.honeywellaidc.com

DECLARATION OF CONFORMITY

42203758-03E	Cable: RS232 TTL, Connector: D 9 Pin F, power on pin 9, TX data on pin 2, coiled Length: 7.7ft. (2.3m)
42203758-03SE	Cable: RS232 TTL, Connector: D 9 Pin F, power on pin 9, TX data on pin 2, straight Length: 7.7ft. (2.3m)
42203758-04E	Cable: RS232 TTL, Connector: D 9 Pin F connector, TX data on pin 2, external power, coiled Length: 7.7ft. (2.3m)
42203758-06E	Cable: RS232 TTL, 9 F 'EP' 15', D 9 PIN F, Mini Din 4 PIN Length: 7.7 ft. (2.3m), coiled
42203764-03E	Cable: Wand Emulation, Power on Pin 9 Connector: D 9 PIN Squeeze Length: 7.7 ft. (2.3m), coiled
42204253-04E	Cable: RS232, black, TX Data on Pin 2 Connector: D 9 PIN F and Mini Din 4 PIN F, 2.3m (7.7'), coiled, external power
42205155-04E	Cable: IBM 46xx, black, RS485 Port 9A/B, 7.0m (23.0'), coiled
42205895-01E	Cable: RS232 TTL, black, coiled, 2.3m (7.7'), power from PS-2 keyboard/mouse port
42206090-01E	Cable: RS232 TTL out Mod 8 Pin M Length: 7.7 ft. (2.4m), straight
42206132-02E	Cable: AT - PS/2 & compatibles, wedge Connector: Mini Din 6 PIN M/F Length: 9.2 ft. (2.8m), coiled
42206132-02SE	Cable: AT - PS/2 & compatibles, wedge Connector: Mini Din 6 PIN M/F Length: 9.2 ft. (2.8m), straight
42206139-04E	100, 3900 RS232 TTL
42206161-01E	Cable: USB, black, Type A, 2.6m (8.5'), straight, host power
42206202-01E	Cable: USB, black, secondary interface Length: 9.2 ft. (2.8m), coiled
42206202-02E	Cable: USB, black, Type A, 2.8m (9.2'), coiled, host powered
42206202-03E	Cable, USB 12 Ft
42206338-01E	Dolphin Series straight USB charging and communications cable (not compatible with 3800g)
42206416-01E	Cable: USB, black, Type A, coiled, 2.6m (8.5'), external power
42206422-01E	Cable: RS232 TTL, black, DB9, 2.3m (7.7'), straight, 5v external power
42206431-01E	Cable: USB, black, Type A, 3.4m (11.1') coiled, host power (Use w/3800VHD-ESD-12E. Not compatible with 3800g)
42206457-01E	Cable, USB, 15' Coiled
42206460-01E	Cable RS232 W/EP, 4600G



Safety and Productivity Solutions

9680 Old Bailes Road
Fort Mill, SC 29707 USA

www.honeywell.com www.honeywellaidc.com

DECLARATION OF CONFORMITY

425388-0406	CABLE, USB A MALE TO USB
427508-0630	CBL ASSY, MINI DN6 M/F
427518-0913	CBL ASSY, D9 M/F 1:1 ST
50101274-001	Cable Black Coiled
50101275-001	Cable DUAL Ended Male
50101284-001	Cable,VS0,3310G
50109842-001	Cable, MB TO HUB 40pin
50111776-001	NGB CBL MB TO VHUB WITH
50111778-001	NGB CBL WIRE HARNESS SA
50113738-001	NGB MB TO IMAGER CBL
50118069-001	USB Multi Checkpoint
50118071-001	RS232 Multi Checkpoint
50126968-001	USB cable, 2.4m
50126968-004	USB Cable, 3M
50130643-001	AUTOCUBE MAIN TO VLD PCBA CBL ASSY
50133276-002	AutoCube Cable, Display, USB, 3m
50133835-001	Wire Harness, twisted, 10pin, ECAP, 1920i
50134004-001	Cable, Grounding, TPH
50135246-001	Cable with Bracket Assy HP
50136415-001	Cable, TPH and Ground Length=60cm
52-52557A-3-FR	MS4980 RS232 Straight
52-52558A-3-FR	MS4980 Keyboard Wedge
52-52559A-3-FR	MS4980 USB Type A
52-52559A-N-3-FR	MS4980 USB Type A
52-52561A-3-FR	Cable, Vuquest 33xx USB
52-52562A-3-FR	Cable, Vuquest 33xx RS232
53-53000H-3	Cable, 9500, RS232, Coil
53-53002G-3	Cable, Black, Wedge, Coil
53-53002G-N-3	Cable, Black, Wedge, Coil
53-53004B-N-3-12	Cable, RS232, Coil, NO
53-53004C-12	Cable, 3.5 meter RS232
53-53020C-3	Cable, Stand Alone KB
53-53089F-3	Cable, Powerlink, RS232



Safety and Productivity Solutions

9680 Old Bailes Road
Fort Mill, SC 29707 USA

www.honeywell.com www.honeywellaidc.com

DECLARATION OF CONFORMITY

53-53101B-3	Cable, RS232, Coil
53-53109D-3	Cable, Powerlink, LSO, coil
53-53153C-3	Cable, POWERLINK, RS232
53-53153C-N-3	Cable, RS232 Coiled
53-53213D-N-3-FR	USB A plus power coil
53-53214C-N-3-FR	USB plus power FS only
53-53235G-3	Cable, USB Type A
53-53235G-N-3	CABLE,USB LS,COIL,DIRECT Ruby Grey
53-53235G-N-3-FR	Cable USB A type- Black
53-53283C-N-3	Cable, USB A, FS,Coil
53-53290C-N-3	Cable, RS232, COIL, DB Male
53-53317A-3	Cable, 8 Pos AUX Cable
53-53802C-N-3	Cable, GSL KBW Coiled No
53-53809C-N-3	Cable, USB Type A No
53-53813D-N-3-11.5	USB coil, no powerlink
54-54088A-3	Cable, strt, RS232, pwrlnk
54-54165A-3	Cable Powerlink shielded
54-54235B-N-3/9.5	Cable USB Type A black
54-54298B	RS232/LP COMM Cable
54-54667A-14	LSO RS232 PWRLNK cable
55-55000C-3	Cable RS232, 9-PIN
55-55002C-3	Cable, KBW w/PWR AT
55-55004A-N-3	Cable Black, no powerlink
55-55235C-N-3	CABLE,5145 USB Straight, Type A 2.9M black
55-55284A-N-3-KY	5145, USB, TYPE A Cable
55-55285A	Cable, 5145 RS232
55-55285A-3-KY	5145, RS232, PWRLNK Cable
55-55286A-N-3-KY	5145, KBW Cable
55-55288A-3	Straight .8 pos mod
55-55535C-N-3	USB Type A 1.9m cable
55-55809B-N-E-3	Cable, GSL USB EAS NO
57-57006B-N-3	Cable, USB Type A, Black
57-57000F-N-3	Cable, RS232 No Pwrlink



Safety and Productivity Solutions

9680 Old Bailes Road
Fort Mill, SC 29707 USA

www.honeywell.com www.honeywellaidc.com

DECLARATION OF CONFORMITY

57-57089D-N-3	Cable,RS232 No Pwrlink
57-57099B-3	Cable AUX Port Black
57-57099B-3-12	12 Feet Stratos AUX
57-57153B-N-3	Cable, RS232 5 Meter No
57-57170-3-5.5C	Scanner AUX cable RS232
57-57201A-N-3	Cable,StratosS,USB,Type
57-57210B-N-3	Cable, RS232 12' No
57-57212B-N-3	Cable, StratosS.IBM, Black
57-57227B-N-3	Cable, StratosS, USB A+
57-57312B-3	Cable,EAS-Checkpoint
57-57499A-3	Cable 7800 RS232 Aux
59-59000-3-YJ	Straight, Cord W/PWR
59-59000C-E-3	Cable, RS232EAS STRAIGHT
59-59000G	Cable, RS232 Straight Pwr
59-59000G-3	Cable RS232 Straight pwr
59-59000G-N-3	Cable RS232 Straight No
59-59002F-3	Cable, KBW, Powerlink
59-59002F-N-3	Cable, KBW, No Powerlink
59-59068D-N-3	Cable, STRT,USB 5V, No
59-59084B-N-3	Cable, USB, 3 meter, Type A
59-59095A-N-3	USB Type A straight
59-59153A-N-3-12WN	Cable, RS232, STRT, SBR
59-59153B-N-3-12	Cable, RS232, STRT, SBR
59-59194C-N-3-14	Cable RS232 14FT STRT NO
59-59200D-N-3	Cable, USB 5V Plus
59-59213A-N-3-FR	Cable, USB A+PWR, 3 meter
59-59235D-N	Cable, USB Type A, gray
5S-5S000D-3	Cable, RS232 12V Link
5S-5S002C-3	Cable, KBW 12V LINK
5S-5S153B-N-3-10	7800 RS232 Straight No
5S-5S213D-N-3	Cable, USB Plus Power No
5S-5S253A-3	7820 RS232 straight 12v

Safety and Productivity Solutions

9680 Old Bailes Road
Fort Mill, SC 29707 USA

www.honeywell.com www.honeywellaidc.com

DECLARATION OF CONFORMITY

5S-5S235D-3	Cable, USB 12V Powerlink
CBL-000-240-C00	CBL,RS232,TTL OUTPUT, 1400G
CBL-000-250-C00	CBL, HSM 5V 232 TTL, 2.5M
CBL-000-300-C00-01	RS232TTL OUT, INDUSTRIAL
CBL-000-300-S00	CBL, PS-2 KBW, HSM 5V
CBL-010-300-C00	CBL, 232 TTL, 9 PIN
CBL-020-035-S00	CBL,RS232,5V,DB9
CBL-020-150-S00-01	Cable, RS232 5V, 1.5M, YJ HF500
CBL-020-270-S00	2.7m RS232 host cable
CBL-020-270-S00-01	Cable, RS232 5V, 2.7M YJ HF500
CBL-020-290-S00	Cable, RS232, Black, DB9, 5V, 2.9M
CBL-020-290-S00-01	Cable, RS232, Black, DB9, 5V, 2.9M IO
CBL-020-300-C00	Cable: RS232 (5V signals), black, DB9 Female, 3m (9.8'), coiled, 5V external power with option for host power on pin 9
CBL-020-300-S00	CBL,232 TTL, 5V
CBL-020-350-S00	Cable, RS232, 5VSIGNAL
CBL-020-500-C00	CBL,RS232TTL,5VSIGNAL,DB
CBL-020-500-C00-01	CBL,RS232TTL,5VSIGNAL
CBL-020-500-S00	Cable, RS232, 5VSIGNAL, DB9
CBL-120-300-C00	Cable: RS232C (+/-12V signals), black, DB9 Female, 3m (9.8'), coiled, 5V external power with option for host power on pin 9
CBL-130-300-S00	Cable, TRUE232,9 PIN D
CBL-140-370-S20-BP	RS232 DB9 Female 3.7m
CBL-220-300-C00	Cable: RS232 (+5V signals), black, DB9 Male, 3m (9.8'), coiled, external power with option for host power on pin 9 for connection to Wincor Beetle
CBL-220-500-S00	CBL, RS232, 5V SIGNAL, DB9
CBL-320-300-C00	Cable: RS232 (+/-12V signals), black, DB9 Male, 3m (9.8'), coiled, external power with option for host power on pin 9
CBL-400-150-S00	Cable is E157914 PRIMAX RU AWM 20099 60C 150V VW-1 CSA LL110529 AWM I/II A/B 60C 150V FT1
CBL-400-190-S00	HDB 15P FM to 10P10C Cable
CBL-400-250-C00	CBL, KEYBOARD EMULATION,1400G



Safety and Productivity Solutions

9680 Old Bailes Road
Fort Mill, SC 29707 USA

www.honeywell.com www.honeywellaidc.com

DECLARATION OF CONFORMITY

CBL-400-250-S00-00	CBL,AUX 5V, 3310G to DATALOGIC, 2.5M
CBL-400-300-C00	CBL, HSM 5V 232 TTL, AUX, 3M
CBL-400-300-S00	cable aux, 5V3310G to statos
CBL-420-300-C00	Cable: RS232 (5V signals), Honeywell Bioptic Stratos Aux, black, 10 pin modular, 3m (9.8'), coiled, host power possible (dependent upon scanner and Stratos models)
CBL-422-300-C00	CBL,RS232 TTL 5V
CBL-500-070-S00	CABLE, USB 5V
CBL-500-120-S00-01	USB Type A to Mini 10pin
CBL-500-120-S00-03	Cable, Micro USB, 1A8, EDA50
CBL-500-120-S00-04	CBL, USB, Micro B to Type A
CBL-500-150-S00	USB Type A HSM 5V 1480mm straight
CBL-500-150-S00-03	CBL USB 1.5M Type A HSM 5V
CBL-500-200-C00	USB Type A HSM 5V
CBL-500-200-S00	USB Type A HSM
CBL-500-200-S00-01	Cable: CBL USB 2M, Type A, HSM
CBL-500-200-S00-02	USB A type to Micro B, 2M
CBL-500-270-S00-01	CBL,USB 5V, 2.7M YJ HF500
CBL-500-290-S00	Cable, USB, Black, Type A, 5V, 2.9M
CBL-500-300-C00	Cable: USB, black, Type A, 3m (9.8'), coiled, 5V host power
CBL-500-300-C00-01	Cable, USB Type A
CBL-500-300-C00-03	Cable: USB Type A, Coiled, 3M
CBL-500-300-C00-04	Xenon RS232 cable
CBL-500-300-S00	Cable: USB, black, Type A, 3m (9.8'), straight, 5V host power
CBL-500-300-S00-02	CBL,USB W/Ferrite, Type A, HSM 5V
CBL-500-300-S00-03	CBL,USB W/Ferrite, Type A,5V Industrial
CBL-500-300-S00-04	CBL, USB Type A, HSM 5V
CBL-500-300-S00-06	CBL, USB Type A, 5V
CBL-500-300-S00-06	CBL, USB Type A, 5V, W/Ferrite
CBL-500-500-C00	Cable: USB, black, Type A, 5m (16.4'), coiled, 5V host power
CBL-500-500-S00	Cable, USB Type
CBL-503-150-S00	CBL,USB RETAIL,12V KEY
CBL-503-300-C00	Cable: USB, black, 12V locking, 3m (9.8'), coiled, 5V host power



Safety and Productivity Solutions

9680 Old Bailes Road
Fort Mill, SC 29707 USA

www.honeywell.com www.honeywellaidc.com

DECLARATION OF CONFORMITY

CBL-503-300-S00	Cable: USB, black, 12V locking, 3m (9.8'), straight, 5V host power
CBL-503-300-S00-01	CBL, USB, 12V KEY, 5V POWER, STRAIGHT
CBL-503-300-S00-02	CBL,USB FS Speed Cable, 3M
CBL-503-500-C00	Cable: USB, black, 12V locking, 5m (16.4'), coiled, 5V host power
CBL-520-290-S00	Cable, USB, Black, Type A, 5V, 2.9M IO
CBL-530-370-S20-BP	USB, Powered, 12V Locking, 3.7m
CBL-532-300-S00	Cable, USBRETAIL,12VKEY
CBL-540-370-S20-BP	USB, Non-powered, 12V
CBL-541-370-S20-BP	USB, Non-powered, Type A
CBL-600-300-S00	Cable, IBM 4683, Port 9B
CBL-600-300-S00-01	CBL, IBM 4683 Port 9D, HSM 5V
CBL-600-400-C00	Cable: IBM 46xx Port 9b, 12V Power, coiled, 4m (13.1')
CBL-601-300-S00	CBL,IBM 46893, Port 9B
CBL-640-370-S20-BP	46xx, IBM-RS485, 3.7m
CBL-700-300-S00	CBL, 232 TTL,HSM 5V
CBL-720-290-S00	Cable, KBW, Black, PS2, 5V, 2.9M
CBL-720-300-C00	Cable: KBW, black, PS2, 3m (9.8'), coiled, 5 V external power with option for host power
CBL-720-300-S00	CBL, PS-2 KBW, 5V
CBL-820-300-C00	WAND EMULATION9 Pin SQZ
CBL-821-300-C00	WAND EMULATION4 Pin SQZ
CBL-860-100-S02	CBL, EAS, Checkpoint, 7980G
CBL-860-200-S04	CBL, EAS, Sensormatic, 7980G
CBL-GIL-300-S00-01	CBL,RS232,TTL,HSM 5V
CBL-GIL-300-S00-02	Cable: RS232 (5V signals), Gilbarco terminal, black, DB9 Female, 3m (9.8'), straight
CBL-MAG-300-C00	CBL,232 TTL,MAGELLAN
CBL-MAG-300-S00	CBL, 232 TTL, MAGELLAN
CBL-MAG-400-C00	CBL, 232 TTL, MAGELLAN, AUX 5V Coiled



Safety and Productivity Solutions

9680 Old Bailes Road
Fort Mill, SC 29707 USA

www.honeywell.com www.honeywellaidc.com

DECLARATION OF CONFORMITY

CBL-NCR-300-S00	Cable: RS232 (5V signals), NCR 787x, black, 8 pin modular, 3m (9.8'), straight, external power with option for 5V host power on pin 1
HR-1C3RB	Cable, RS232, FOR KEYENCE
HR-1C3RC	Cable, TRUE232, 9PIN D
HR-1C3VC	Cable, KBW, COILED, 3M
HR-1C3UC	Cable, USB TYPE
HR-1C3UN	Cable, USB Type
HR-1C5UC	Cable, USB TYPE
CBL-500-300-S00-07	CBL, USB TYPE A, 5V, W/
CBL-600-300-S00-02	CBL, IBM 4683 PORT 9B,
CBL-500-300-S02	Cable: USB, Checkpoint EAS with interlock, Black, Type A, 3m (9.5') for 7190g
CBL-801-300-C00	CBL, RS232, GRANIT TO VOCOLLECT TALKMAN, Host 5V power only, 3M, COILED
CBL-801-370-C00	CBL, RS232, GRANIT TO VOCOLLECT TALKMAN, Host 5V power only, 3.7M, COILED
CBL-500-150-S00-01	TIANMA USB CABLE
CBL-500-270-S00	CBL, USB TYPE A 5V,
CBL-500-300-S00-01	CABLE, USB TYPE
CBL-500-290-S00-01	CBL, USB TYPE A, 5V,
CBL-500-200-S00-03	CABLE, USB TYPE A,5V,2M
CBL-500-300-S00-05	CBL, USB TYPE A, 5V,
CBL-500-150-S00-02	CBL USB 1.5M TYPE A HSM
CBL-720-150-S00	CBL PS-2 KEYBOARD WEDGE
CBL-020-150-S00	CABLE, RS232 5V, 1.5M,
CBL-720-270-S00	CBL PS-2 KEYBOARD WEDGE
CBL-000-762-C00	CABLE, COILED, RS232 TTL OUTPUT
CBL-200-500-S00	Cable: RS232, black, DB9 Male, 5m (16.3'), straight, 5V host power
CBL-432-300-S00	CABLE,RS232,12VSIGNAL,VERIFONE,8 PINMOD
CBL-500-300-C00-05	CBL, USB TYPE A, COILED, 3M, FOR L-TRON
CBL-720-370-C00	CBL, PS-2 KEYBOARD WEDGE, COILED, 5V
42203758-01E	CABLE,RS232 TTL,POWER ON PIN 9,TX DATA



Safety and Productivity Solutions

9680 Old Bailes Road
Fort Mill, SC 29707 USA

www.honeywell.com www.honeywellaidc.com

DECLARATION OF CONFORMITY

42206431-01E	CABLE, USB TO PS/2 KEYBOARD CABLE
50113891-001	CABLE,VOCOLLEC 48"
CBL-500-100-S00	CBL, USB Type A, 5V
50145804-001	USB Type A White HSM 5V
CBL-120-300-S00	CBL, TRUE232, 9 PIN D Female, 5V, 7980G
50148058-001	CBL, EXTERNAL, RS232, DB25F, 5M, HF800
50143315-002	CBL, ETHERNET, M12 CONN TO RJ45, 5M, HF800
CBL-500-100-S00-02	CBL, USB, TYPE A, 5V, 7980G

Signed for and on behalf of	Honeywell International Inc	
Place and Date of Issue	9680 Old Bailes Road Fort Mill, SC 29707 USA	29-May-2019
Name and Title	Martyn Rowe Manager Product Stewardship Honeywell Safety and Productivity Solutions (SPS).	
Signature		