

PSDS

12

Product Safety Datasheet

These products are classified as Articles under REACH and are not subject to the requirements for Information in the Supply Chain (Safety Data Sheets and Labels). While sensors may release hazardous substances if damaged, this is not an intended release as defined under REACH. Sensors are not classified as hazardous under the CLP.

1. Product Name / Chemical Identification

Electrochemical sensors with internal filter to detect Carbon Monoxide (CO).

2CF 2CF-3 LoCO-2 LOC03

Manufacturer: Honeywell, Walton Rd, Portsmouth, Hampshire, England, PO6 1SZ

Telephone: +44 23 9228 8100

Fax: +44 23 9238 6611

Website: <https://sps.honeywell.com/us/en/products/sensing-and-iot/sensors/gas-sensors>

2. Composition / Information on Ingredients

Electrolyte containing sulphuric acid (H₂SO₄), Filter Material, proprietary catalyst alloy electrodes, enclosed in a plastic based housing with attached metal connections.

3. Hazards Identification

The electrolyte inside the sensor constitutes the main potential hazard. This may leak out should the housing be damaged or tampered with.

3.1. Inhalation of electrolyte:

Inhalation is not an expected hazard unless heated to high temperatures. Mist or vapour inhalation can cause irritation to the nose, throat, and upper respiratory tract.

3.2. Ingestion of electrolyte:

Corrosive. May cause sore throat, abdominal pain, nausea, and severe burns of the mouth, throat, and stomach.

3.3. Skin or eye contact of electrolyte:

Corrosive. May cause redness, pain, blurred vision and eye burns.

3.4. Aggravation of pre-existing conditions:

Persons with pre-existing skin disorders or eye problems, or impaired respiratory function may be more susceptible to the effects of the substance.

4. First-Aid Measures

In case of leakage and:

4.1. Eye contact with electrolyte:

Irrigate thoroughly with water for at least 15 minutes. Obtain medical advice.

4.2. Inhalation of electrolyte:

Remove to fresh air. Rest and keep warm. Obtain medical advice if applicable.

4.3. Skin contact with electrolyte:

Immediately flush the skin thoroughly with water for at least 15 minutes. Remove contaminated clothing and wash before re-use. Obtain medical advice if continued irritation.

4.4. Ingestion of electrolyte:

If swallowed DO NOT INDUCE VOMITING. Wash out mouth thoroughly with water and give plenty of water to drink. Obtain medical advice.

5. Fire Fighting Measures

5.1. Fire:

Not considered to be a fire hazard.

5.2. Explosion:

Not considered to be an explosion hazard.

5.3. Fire extinguishing media:

Use any means suitable for extinguishing surrounding fire.

6. Accidental Release Measures

6.1. Damage

Should any CiTiceL[®] be so severely damaged or tampered with that the leakage of the contents occurs then the following procedures should be adopted:

- Avoid skin contact with any liquid or internal component through the use of protective gloves.
- Disconnect CiTiceL[®] if it is attached to any equipment.
- Use copious amounts of clean water to wash away any spilt electrolyte, particularly important in equipment because of the corrosive nature of the electrolyte.
- Observe first aid measures in case of eye contact, inhalation, skin contact or ingestion of electrolyte.

7. Handling and Storage

Must not be exposed to temperatures outside the range specified on the specification sheet.

Should not be exposed to organic vapours, may cause physical damage to the body of the sensor.

Must not be stored in areas containing organic solvents or in flammable liquid stores.

8. Exposure Controls / Personal Protection

None in normal operation

9. Physical and Chemical Properties

Sensor is a sealed unit

10. Stability and Reactivity

N/A

11. Toxicological Information

Electrolyte is corrosive to eyes, respiratory system and skin.

12. Ecological Information (relevant if sensor becomes damaged)

Harmful effect on aquatic organisms. Harmful effect due to pH shift.
Toxic effect on fish and algae.

13. Disposal Considerations

Contains toxic compounds irrespective of physical condition. Should be disposed of according to local waste management requirements and environmental legislation.

Should not be burnt since they may evolve toxic fumes.

14. Transport Regulations

Honeywell electrochemical sensors are classified as “batteries wet non-spillable” (UN2800). They are transported as per IATA PI 872 and 49CFR 173.159a, and need no special packaging, labels etc. as they are not restricted as per IATA Special Provision A67.

15. Regulatory Information

R-Phrases: 35

Causes severe burns.

S-Phrases: 26-30-45

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Never add water to this product. In case of accident or you feel unwell, seek medical advice immediately.

WARRANTY/REMEDY

Honeywell warrants goods of its manufacture as being free of defective materials and faulty workmanship during the applicable warranty period. Honeywell's standard product warranty applies unless agreed to otherwise by Honeywell in writing; please refer to your order acknowledgment or consult your local sales office for specific warranty details. If warranted goods are returned to Honeywell during the period of coverage, Honeywell will repair or replace, at its option, without charge those items that Honeywell, in its sole discretion, finds defective. **The foregoing is buyer's sole remedy and is in lieu of all other warranties, expressed or implied, including those of merchantability and fitness for a particular purpose. In no event shall Honeywell be liable for consequential, special, or indirect damages.**

While Honeywell may provide application assistance personally, through our literature and the Honeywell web site, it is buyer's sole responsibility to determine the suitability of the product in the application.

Specifications may change without notice. The information we supply is believed to be accurate and reliable as of this writing. However, Honeywell assumes no responsibility for its use.

FOR MORE INFORMATION

Honeywell Advanced Sensing Technologies services its customers through a worldwide network of sales offices and distributors. For application assistance, current specifications, pricing, or the nearest Authorized Distributor, visit sps.honeywell.com/ast or call:

USA/Canada	+302 613 4491
Latin America	+1 305 805 8188
Europe	+44 1344 238258
Japan	+81 (0) 3-6730-7152
Singapore	+65 6355 2828
Greater China	+86 4006396841

Honeywell Advanced Sensing Technologies

830 East Arapaho Road
Richardson, TX 75081
sps.honeywell.com/ast

CITiceL® is a trademark or registered trademark of Honeywell International, Inc. in the United States and other countries.

002742-7-EN | 7 | 11/21
ECN-00008103
© 2021 Honeywell International Inc. All rights reserved.

